PRODUCT DATA SHEET

HOSPITAL PRODUCTS



SAFETOUCH™ CATH (WINGED)

STERILE, SINGLE-USE CATHETER WITH SAFETY DEVICE FOR IV INFUSION

NIPRO

SAFETOUCH™ CATH (WINGED)

STERILE, SINGLE-USE CATHETER WITH SAFETY DEVICE FOR IV INFUSION

- Irreversible, passive safety mechanism
- Audible click confirms locking of safety device
- Does not require a change in puncture technique
- Radiopaque
- Ultra sharp three-beveled needle to minimize discomfort
- Siliconization of needle minimizes penetration and gliding force
- Flexible wings for easy grip
- Color-coded wings and hub to indicate gauge
- Transparent PUR catheter tube for quick visualization of blood in the flashback chamber to facilitate insertion
- Flashback in hub means the needle is correctly in the vein
- Flashback in catheter means the catheter is correctly in the vein
- Not made with latex, DEHP or PVC
- Available in 16-24 G
- IV infusion duration: hours to several days
- For use by healthcare professionals only

CE 0123
Class IIa Medical Devices
Rule 7
MDD 93/42/EEC
UMDNS 18331

PRODUCT COMPLIANCE

- CE-marked, Class IIa Medical Devices, Rule 7, MDD 93/42/EEC, UMDNS 18331
- Complies with the following norms, directives, and regulations:
  - ISO 594-1:1986
  - ISO 594-2:1998
  - ISO 2859-1:1999 /AMD 2011
  - ISO 7864:1993
  - ISO 10555-5:2013
  - ISO 10993-10:2010
  - ISO 14644-4:2001
  - ISO 23908:2011
- Labels contain 26 languages

MANUFACTURING DETAILS


Legal manufacturer: Nipro Corporation

Country of origin: Thailand

STERILIZATION AND SHELF LIFE

Sterilization	Single-use only	Indicator sticker	Shelf life
EtO (Ethylene oxide) STERILE EO		Each outer box (or shipping carton) contains a chemical indicator that indicates sterility. This indicator comes in the form of a [violet] sticker that turns [blue] when sterilized.	5 years

MATERIALS USED



Needle (cannula)
Material: Stainless steel SUS-304

Cutting angle
Three-beveled

Lubricant
Material: Silicone Polydimethylsiloxane

Catheter tube
Material: Polyurethane (PUR)

Caulking pin
Material: Stainless steel SUS-304

Catheter wing
Material: Polypropylene (PP)

Safety ring
Material: Polyoxymethylene (POM)

Catheter hub
Material: Polypropylene (PP)

Protector
Material: Stainless steel SUS-304?

Needle hub
Material: Polycarbonate (PC)

Glue
Material: Acrylic resin

Vent fitting
Material: Polypropylene (PP)

Membrane filter
Material: Random microglass filter

Not made with
Latex, DEHP or PVC

PRODUCT RANGE OVERVIEW

Reference code	Description	Purpose	Flow rate not less than	Color
NIC-SF-1650PW-ET	IV Cath SF wing 16Gx2" (1,7x50mm) PUR	IV	⩾ 162 ml/min	
NIC-SF-1832PW-ET	IV Cath SF wing 18Gx1 1/4" (1,3x32mm) PUR	IV	⩾ 81 ml/min	
NIC-SF-1850PW-ET	IV Cath SF wing 18Gx2" (1,3x50mm) PUR	IV	⩾ 81 ml/min	
NIC-SF-2032PW-ET	IV Cath SF wing 20Gx1 1/4" (1,1x32mm) PUR	IV	⩾ 49 ml/min	
NIC-SF-2050PW-ET	IV Cath SF wing 20Gx2" (1,1x50mm) PUR	IV	⩾ 49 ml/min	
NIC-SF-2225PW-ET	IV Cath SF wing 22Gx1" (0,8x25mm) PUR	IV	⩾ 29 ml/min	
NIC-SF-2232PW-ET	IV Cath SF wing 22Gx1 1/4" (0,8x32mm) PU	IV	⩾ 29 ml/min	
NIC-SF-2419PW-ET	IV Cath SF wing 24Gx3/4" (0,7x19mm) PUR	IV	⩾ 17 ml/min	
NIC-SF-2425PW-ET	IV Cath SF wing 24Gx1" (0,7x25mm) PUR	IV	⩾ 17 ml/min	

PACKAGING DETAILS

Reference code	Individual unit			Inner box					Outer box					
	Gauge (G)	Length (mm)	Net weight (g)	Quantity	L (mm)	W (mm)	H (mm)	Gross weigth (g)	Quantity	L (cm)	W (cm)	H (cm)	Gross Weight (kg)	m^3
NIC-SF-xxxxPW-ET	xx	xx	0,98	50	206	63	145	284	2000	662	429	319	12,22	0,0906

Languages

26 languages on IFU, and all levels of packaging:

English (EN), Bulgarian (BG), Czech (CS), Danish (DA), German (DE), Greek (EL), Spanish (ES), Estonian (ET), Finnish (FI), French (FR), Croatian (HR), Hungarian (HU), Italian (IT), Lithuanian (LT), Latvian (LV), Dutch (NL), Norwegian (NO), Polish (PL), Portuguese (PT), Romanian (RO), Russian (RU), Slovakian (SK), Slovenian (SL), Serbian (SR), Swedish (SV), Turkish (TR)

Transport conditions

Closed and dry

Storage conditions

Open the packaging only immediately before use to guarantee sterility.

Label details

	Individual unit	Inner box	Outer box
Product name	✓	✓	✓
Product size	✓	✓	✓
Quantity (pieces)	—	✓	✓
REF	✓	—	—
LOT	✓	—	—
	✓	—	—
STERILE EO	✓	✓	✓
CE	✓	✓	✓

	Individual unit	Inner box	Outer box
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
	✓	✓	✓
EC REP	✓	✓	✓
	—	✓	✓
	✓	✓	✓

NIPRO Live Longer. Live Better.
NIPRO Corporation
3-26 Senriokashinmachi, Settsu-shi, Osaka 566-8510, JAPAN. | www.nipro.co.jp